



232 Branford Rd.
North Branford, CT 06471
Orders: 203.481.9460
Tech: 203.481.9943
Fax: 203.481.9641

Product Instructions

#26-050 #26-150 Pleated Ultra Fine Screen Filter Elements

These filter elements are cleanable and reusable and specifically designed for CM spin-on, canister, and inline oil filters using 2-5/8" or 4-5/8" elements.

Their 400 mesh screen media filters down to 40 microns and will clean out all engine damaging debris. They are designed for race applications where oil is clean and frequently inspected and changed. In other applications they should be used as a secondary inspection filter.

Filter is designed to flow from the outside to the inside as in a standard spin on filter.



FILTER ELEMENT INSPECTION / INSTALLATION:

- 1) Remove filter from engine and drain oil into appropriate container.**
- 2) Use care and take your time removing the end cap from the filter body so as not to damage the finish or housing. For filters with spin-on end caps use a strap wrench to hold the filter body and unscrew the end cap with an adjustable wrench. For filters with bolt on end caps, remove the four bolts and lift the cap off the filter body.**
- 3) Inspect the element for indications of engine damage or excessive contamination.**
- 4) Inspect seals for damage and replace as needed.**
- 5) Thoroughly oil cap seal and reinstall cap and element.**
- 6) Tighten filter cap snug only. DO NOT OVERTIGHTEN.**